

DART SERVICE INSTRUCTION

TO AMEND INSTALLATION INSTRUCTIONS IIN-D350-727 REV. B OR LATER APPROVED REVISION
REF. TCCA PDA: PDA05-18

1.0 PURPOSE

Due to variation in the wearplate hole locations on some skid tubes, the Dart wearplates may not align. Therefore D3319-X, D5465-X, or D5478-1 Wearplates may be supplied with undrilled tabs to facilitate installation. The purpose of this Dart Service Instruction is to provide instructions to allow for customers to locate and drill holes when receiving wearplates without attachment holes.

2.0 CHANGE

Install wearplates per IIN-D350-727. During installation, transfer drill any undrilled tabs as follows:

1. Locate the wearplate to the skid tube using existing holes.
2. Transfer mark undrilled holes from the skid tube to the wearplate.
3. Drill $\varnothing 0.316$ " holes in the wearplate at the transfer mark locations. Ensure minimum edge distance of 0.300" remains.
Note: It is acceptable to slot the holes up to 0.546" long x 0.316" wide to ensure alignment, as long as the edge distance does not fall below 0.300".
4. Deburr holes and complete installation per IIN-D350-727.

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-O-01

APPROVED

BY: C. PROVENCAL (DE # 03)

DATE: 19.02.22
CERT. NO.: PDA05-18
ISSUE NO.: 3

APPROVED

A	NEW ISSUE	NO	19.02.22
REV.	DESCRIPTION	BY	DATE
DESIGN	NO	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	NO		
CHECKED	ZF	DRAWING NO.	REV. A
MFG. APPR.	N/A	DSI 9822	SHEET 1 OF 1
APPROVED	NO	TITLE	SCALE
DE APPR.	CP	WEARPLATE INSTALLATION	NTS
DATE	19.02.22	COPYRIGHT © 2019 BY DART AEROSPACE LTD. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	